

E300L

Retail ATM

The E300L is a low-cost retail ATM, built to comply with all industry standards you expect from a high end machine including ADA, PCI EPP, UL and Triple DES. Featured with low cost of ownership, high visibility and easy accessibility, E300L will be an ideal choice for markets of any environment.



E300L Retail ATM

SPECIFICATIONS

Embedded PC

- ◆ Intel Celeron-M 600MHz CPU, 512M DDR
- ◆ 2G Compact Flash (extendable)

Display

- ◆ 10.4" TFT color LCD
- ◆ Digitized voice guidance

Operator Interface

- ◆ Front Service Panel
- ◆ User-friendly Maintenance Manager
- ◆ Privilege management with supervisor menu in English
- ◆ Self-diagnosis & error inquiring
- ◆ E-journal output

Keypad

- ◆ Tactile 4 X 4 numeric metal keypad
- ◆ 2 X 4 Function Display Keypad
- ◆ PCI EPP
- ◆ Vandal resistant & dust proof
- ◆ Beep responding on key press

Card Reader/Writer

- ◆ DIP card reader (magnetic, Hi-Co track 1/2/3 read)
- ◆ DIP card reader/writer (smart card, EMV certified) (optional)
- ◆ Motorized card reader/writer (magnetic/smart card, Hi-Co track 1/2/3 read and write, EMV certified.) (optional)

Printer

- ◆ Graphical Receipt Printer
 - High-speed graphics USB thermal printer
 - Local character printing

Dispenser

- ◆ High-speed dispenser
 - Frictional spray dispensing
 - Dispensing speed: 7 notes per second
 - Max.40 notes per transaction
 - Note cassette: standard 1, maximum 3
 - Note Cassette capacity: up to 2000 notes
 - Reject Vault capacity: up to 100 notes

Security

- ◆ Physical:
 - UL 291 Business Hour
 - UL 291 Level 1 (optional)
 - Electronic combination lock
 - Mechanical combination lock (optional)
- ◆ PCI EPP
- ◆ EMV Level 2 certified

Software

- ◆ Operating system: Windows XPE
- ◆ ATM application software:
 - NDC/NDC+ emulation
 - DDC emulation
 - ISO8583 emulation
 - Triton emulation
 - Standard CEN/XFS SP
 - Can be customized to comply with any ATM switching system

Network Communication

- ◆ Standard TCP/IP
- ◆ Wireless connection: GPRS/CDMA (optional)

Working Environment

- ◆ Operating Temperature:
 - 50°F (10°C) to 104°F (40°F)
- ◆ Relative humidity:
 - 20% to 80%
- ◆ Non-condensing

Power Consumption

- ◆ AC110-240V~, 50Hz
- ◆ 120 watts maximum

Dimensions & Weight

- ◆ Width: 17.5 in.
- ◆ Depth: 25.2 in.
- ◆ Height: 49.6 in.
- ◆ Weight: 231.5lbs (105kg)

GRG International.

300 Davis Avenue Suite 200
Pass Christian, MS 39571
Tel: 228-452-5000
Fax: 228-452-5005
E-mail: Sales@grgatm.com

Copyright by GRG Banking Equipment Co., Ltd.
All rights reserved.

Specifications are subject to update without prior notice.
Please consult GRG Banking or its representative for the

www.grgatm.com